

REDUCE POWER CONSUMPTION WITH KODAK CTP SOLUTIONS

With over 30 years of experience designing and manufacturing thermal CTP devices in its own facilities, Kodak has continued to innovate in order to optimize performance while reducing environmental impact. Our latest models enable significant power savings—over both our previous CTP devices and the competition—without compromising on productivity or uptime. Kodak's patented technology and tight integration between R&D, manufacturing and service help ensure benchmark reliability and long system life.

	POWER CONSUMPTION WHILE IMAGING (WATTS)*				
	Current Model	**Competitor A****	**Competitor B****	**Competitor C****	**Competitor D****
KODAK ACHIEVE T400 Platesetter	**380**	4,970 **92% savings**	4,600 **92% savings**	700 **46% savings**	5,300 **93% savings**
KODAK ACHIEVE T800 Platesetter	**380**	4,970 **92% savings**	4,000 **91% savings**	3,000 **74% savings**	5,600 **93% savings**
KODAK TRENDSETTER Q400 Platesetter (F/X-Speed)	**770**	4,980 **85% savings**	4,600 **92% savings**	3,000 **74% savings**	5,300 **85% savings**
KODAK TRENDSETTER Q800 Platesetter (F/X-Speed)	**770**	4,980 **85% savings**	3,900 **80% savings**	3,000 **74% savings**	5,600 **86% savings**
KODAK MAGNUS Q800 SCU (F/X-Speed)	**1596**	4,970 **48% savings**	3,900 **48% savings**	3,000 **28% savings**	8,600 **75% savings**
KODAK MAGNUS Q800 MCU/MPL (F/X-Speed)	**2158**	4,970 **57% savings**	3,900 **45% savings**	3,000 **28% savings**	8,600 **75% savings**

*Based on public information.
**Competitive devices are those that are comparable in terms of specifications and features.

KODAK CTPs USE LESS POWER BY DESIGN:

- State-of-the-art electronics
- Custom-designed power distribution system
- Low-current draw drum drive system
- High-efficiency imaging system
- High-efficiency cooling system
- Optimized mechanical assemblies

KODAK.COM/GO/CTP

Eastman Kodak Company 343 State Street Rochester, NY 14650 USA
©Kodak, 2026. KODAK, ACHIEVE, MAGNUS, TRENDSETTER and the KODAK Logo are trademarks of Kodak. K-1017-26.09.04.EN.02